

HOW TO SPRAY BUFF A FLOOR

Tools & Materials Needed:

- 175 to 1000 rpm floor machine
- Red pads
- Trigger sprayer bottle
- Dust mop
- "Wet floor" signs

Products:

1. Spray buff solution
2. Dust mop/dust cloth treatment

Procedures:

Purpose of Spray Buffing

- Fill in scratches in finish.
- Bring back gloss lost to heavy foot traffic.
- Extend periods between stripping or scrubbing.

Procedures for Spray Buffing

Put on gloves and glasses.

- Start with a freshly dust mopped floor.
- Fill trigger sprayer with spray buff solution.
- Adjust spray nozzle to a fine mist.
- Place red pad on the floor machine.
- Lightly spray the area in front of the machine or on the right side.
- Spray an area 3 feet by 3 feet.
- Do not over spray solution.
- All product must be buffed dry.
- Floor will remain dull if insufficient buffing done.
- Floor will appear smeary at first.
- As spray buff solution dries, the shine will come back.
- The scuff marks should be gone.
- If black heel marks are on the floor, a water dilutable spray buff product with a solvent should be used.
- Change pads frequently.
- Repeat process by spraying another area 3 feet by 3 feet, in front or to the right, until the entire area has been spray buffed.
- Dust mop the entire area that was spray buffed.
- Put away equipment
- Put away all equipment, tools and materials.
- Wash out spray buff pads.
- If pads are too built up, soak in diluted stripper solution.
- Always wear your gloves when working with stripper.