

ABILITY

Low Maintenance Floor Finish

Unique multi-polymer finish offers maximum in shine, resists scratching, and prolongs time between stripping. Crystal clear, mirror image floor finish. May be used on all resilient flooring and most sealed, non-resilient flooring. Extremely hard, durable finish protects your floor and makes for easy clean-up and removability. High gloss, tough protection, and easy maintenance ensure value and make a nice reflection on you. The exceptional choice for educational and retail facilities where little to no time is available for constant floor burnishing. Recommended for low to medium maintenance procedures.



PRODUCT INFORMATION:

- High gloss, low maintenance and ultimate durability
- Multi-polymer formula for highest shine, reduced scratching and extended life
- Superior hardness and ease of removability for least amount of labor

pH 8.0 - 9.0
Form Liquid
Fragrance Acrid
Color White
Packaged 4/1 Gallon, 5 Gallon Pail & 55 Gallon Drum

DIRECTIONS FOR USE:

INITIAL APPLICATION: Completely strip all old wax or finish. Be careful to follow the "Directions for Use" for the selected stripper. Remove the stripping solution with a shop vac or conventional mop and perform a final detail mopping with clear water to remove all stripper residue. Allow floor to completely dry. Repeat if necessary. Floor must be clean, dry and free of all residue. Apply 1 or 2 even coats of sealer (optional, based on condition of floor), and let dry. Apply finish in uniform, thin to medium coats. Allow each coat to dry for 20 to 30 minutes, or until surface is completely dry to the touch, before applying additional coats. Allow an extra 10 minutes drying time for each additional coat. Total of 4-6 coats of finish are recommended.

ROUTINE MAINTENANCE: Sweep large debris and remove. Dust mop to remove dry soil, then damp mop or automatic scrub with a neutral cleaner. Buff or burnish the floor as desired. Use of a cleaner/restorer is recommended to extend time between top scrub and recoating.

INTERIM MAINTENANCE: Sweep large debris and remove. Dust mop to remove dry soil, then damp mop or automatic scrub with a neutral cleaner. Top scrub with top scrub cleaner and recommended floor pad to remove top soiled layers of finish. Floor must be clean, dry and free of all residue. Apply 1-2 coats of finish as directed under "Initial Application" on this label.

KEEP FROM FREEZING: Slip resistance meets or exceeds ASTM D 2047-04 James Machine 0.5 minimum.

IMPORTANT SAFETY INFORMATION:

Non-hazardous according to OSHA GHS Hazard Communication Standard (29CFR1910.1200).

If medical advice is needed, have product container or label at hand. Keep out of reach of children. Read label before use. Store in cool, dry conditions in well sealed receptacles. Dispose of contents and container in accordance with local, regional, national and international regulations. Dispose of contents and container in accordance with local, regional, national and international regulations.

FIRST AID: IF ON SKIN: Generally the product does not irritate the skin. Rinse with warm water. If skin irritation continues, consult a doctor. **IF IN EYES:** Remove contact lenses if worn. Rinse opened eye for several minutes under running water. Then consult a doctor. **IF INHALED:** Supply fresh air; consult doctor in case of complaints. **IF SWALLOWED:** Do not induce vomiting; call for medical help immediately. Rinse out mouth and then drink plenty of water.

Emergency Response Number ChemTel Inc. 1-800-255-3924

SOLUTIONS FOR A CLEANER WORLD™



THEOCHEM LABORATORIES, INC. 7373 Rowlett Park Drive • Tampa, Florida 33610 • (813) 237-6463 • www.theochem.com

MADE IN
USA
100447-1013v1